

Orthogonal Fusion; Improving Resolution for Multispectral Segmentation

Jose Tamez-Pena, PhD., Kevin Parker, PhD., Edmund Kwok, PhD., Gwy Suk Seo, MD, PhD, Saara M.S. Totterman, MD, PhD,
Department of Radiology and Electrical Engineering, University of Rochester Medical Center

Introduction

The segmentation algorithms which are

same structures which were used for 2-D evaluation, was evaluated and compared.

intensive. Previous studies have shown that accurate segmentation of MRI data of the brain for either 2D or 3D presentation requires the use of multispectral data (1). Several algorithms have been developed to allow the accurate fusion of two or more MR brain data sets (2). To improve the segmentation of musculoskeletal structures we developed an algorithm to register and fuse two orthogonal 3D musculoskeletal MR imaging data sets and tested its feasibility in automatic segmentation of the knee and shoulder structures.

In the 2-D data sets the cartilage and the labri of the shoulder were better delineated using two channel data compared to the one channel data. In the fused data sets isotropic volume allowed high resolution visualization of cartilage and the labri in any arbitrary plane. The segmentation of cartilage and the labri from the fused data sets was more accurate than from the single channel data set.

In the knee the fused data sets visualized the cartilage and meniscus more clearly than a single data set. In fused data sets the cartilage and menisci were seen clearly in all arbitrary planes. Also in the knee the segmentation of the cartilage and menisci was more

Material and Method

We developed an algorithm where two

by maximizing the correlation between gradient magnitude. Once the orthogonal images were registered they were fused to reconstruct a single isotropic high resolution volumetric image. The isotropic image was reconstructed first by assuming that an individual voxel on an MR image is an average of the magnetic

Conclusion

Fusing two orthogonal 3D MR imaging sets creates the single isotropic volume. This isotropic volume provides higher resolution data than single channel data allowing high resolution 2-D analysis in

Then we modeled this process as the projection of the MR properties into a single sensor. This model allowed us to derive a set of linear equations that can be used to recover the MR properties of every single voxel of the isotropic volume given only two orthogonal 3D MR images. We used projections on convex sets (POCS) to solve a set of linear equations. The reconstruction of high resolution images from the fusion of the two orthogonal sets using the proposed approach is equivalent to the filtering backprojection algorithm used for the reconstruction of CT images.

clinical setting when small focal cartilage lesions in knees or wrists or fingers need to be evaluated. The fused data sets improved the segmentation of the anatomic structures including cartilage. Fusing the two orthogonal data sets acquired with different imaging parameters may in the future provide more accurate automated segmentation of musculoskeletal structures, especially for cartilage.

MR imaging data sets of two shoulders and three knees were acquired on a 1.5 Tesla Signa Horizon

References

1. Vinitiski S, Gonzalez C, Mohamed FB, et al. Improved intracranial lesion characterization by tissue

and axial or coronal and sagittal planes with a 10 or 11 cm FOV, 256 x 256 matrix and 1.5 mm slice thickness. TE was adjusted to produce either T1 or T2 star-weighted information. One of the data sets was also fat

Med 1997;37:457-469.

2. Vinitiski S, Gonzalez C, Knobler K, et al. Fast tissue segmentation based on a 4D feature map in

data sets and single fat suppressed image data sets were then segmented using our segmentation algorithm.

Imaging 1999;9:768-776.

The feasibility of the approach was tested on MR images of the knee and shoulder. In 2-D images the visualization of cartilage and labri in the shoulder and cartilage and menisci in the knee were evaluated and

In the segmented images the segmentation of the